

产品选型

CCY	差压变送器									
代号		变送器类型								
30	微差压型（默认无连接线）									
代号		有无显示								
P		无显示								
X		有显示								
代号		量程范围								
69		0~100Pa								
70		0~200Pa								
71		0~500Pa								
01		0~1kPa								
02		0~2kPa								
94		0~3kPa								
95		0~4kPa								
03		0~5kPa								
04		0~10kPa								
72		±100Pa								
73		±200Pa								
74		±500Pa								
36		±1kPa								
37		±2kPa								
96		±3kPa								
97		±4kPa								
38		±5kPa								
39		±10kPa								
67		定制								
代号		信号输出								
A1		4~20mA				两线制				
RS		RS485通讯接口， 标准MODBUS通讯协议				四线制				
V5		0~5VDC				三线制				
V10		0~10VDC				三线制				
V4		1~5VDC				三线制				
DZ		定制								
代号		连接方式								
B1		Φ6宝塔嘴								
B2		Φ8宝塔嘴								
K		Φ6快接口								
N		Φ4快拧接口								
44		定制								
代号		精度等级								
B		0.25%FS								
C		0.5%FS								
D		1%FS								
DZ		定制								
代号		供电电压								
G		12~36VDC								
G4		12~24VDC（本安防爆专用）								
G5		9~36VDC								
DZ		定制								
代号		防爆类型								
B		本质安全型（仅限电4~20mA输出）								
F		粉尘本质安全型（注1）								
无		标准型（无防爆）								
代号		定制								
D		其他定制要求								
无		常规								
CCY	30	P	69	A1	B1	D	G5			选型举例
例如： CCY30-P-69-A1-B1-D-G5(CCY30微差压变送器、无显示、量程0~100Pa、输出4~20mA、连接Φ6宝塔嘴、精度1级、供电9~36VDC)										
注1： 仅限4~20mA输出（无显示）										